

Celebrity[®] XL8

The all-new Celebrity[®] XL8 takes scooters to a new level of refinement convenience and performance. With a standard delta tiller with wraparound handles, independent console angle adjustment, deluxe high-back reclining captain's seat, full directional light package and one-handed tiller angle adjustment, the Celebrity XL8 is our most feature filled scooter in its class.



Celebrity[®] XL8
Shown in Red



Pride
Mobility Products Ltd.

Unit 106, Heyford Park, Camp Road
Upper Heyford, Oxfordshire, OX25 5HA
Tel: 44 1869 233 100
Fax: 44 1869 233 400



www.pridemobility.com

Celebrity[®] XL8

Specifications:

WEIGHT CAPACITY:	159kg (25 STONE)
MAXIMUM SPEED:	Up to 13 km/h (8 mph)
GROUND CLEARANCE:	11 cm (4.25")
TURNING RADIUS:	168.27 cm (66.25")
LENGTH:	130.17 cm (51.25")
WIDTH:	64 cm (25.25")
FRONT TYRES:	10 cm x 33 cm (4" x 13")
REAR TYRES:	10 cm x 33 cm (4" x 13")
ANTI-TIPS:	Rear
STANDARD SEAT:	Deluxe reclining high-back
SUSPENSION:	Front and rear
BATTERY CHARGER:	Off-board
PER-CHARGE RANGE:**	Up to 48 km (30 miles)
BATTERIES:	2 x 30 amp (standard) or 2 x 40 amp (optional)
BATTERY WEIGHT:	30 amp: 11 kg (24.5 lbs.) each 40 amp: 14 kg (31 lbs.) each
TOTAL WEIGHT w/o BATTERY PACKS:	91 kg (200 lbs.)
HEAVIEST PIECE WHEN DISASSEMBLED:	37.65 kg (83 lbs)

Colours:



Red

Features:

- State-of-the-art rear suspension
- Maximum speed up to 13 km/h (8 mph)
- Maximum weight capacity of 159 kg (25 STONE)
- Ultra-simple, auto-latching lock-up for quick disassembly/reassembly
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket standard
- Tight turning radius of 150 cm (59")
- Includes standard angle-adjustable dual bulb kerb light
- Front frame-mounted seat post for optimal stability
- Standard removable battery charger storage bag
- High visibility reflectors
- Microprocessor based controller
- Tiller rotation lock permits tiller to be used as handle during transport

Options:

- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Walker holder
- Upgrade to 40 amp batteries

The information contained herein is correct at the time of publication, due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

**Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.*