

Jazzy® GO-2

The Jazzy® Go-2 delivers high performance manoeuvrability and efficiency in a compact, stylish package. A powerful PG GC programmable controller, in-line motors, and enhanced battery size are just a few of the features that make the Jazzy Go-2 an excellent overall value.



Jazzy® Go-2
shown in Red

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.com

BUILT WITH PRIDE
Pride
Mobility Products Ltd.

SPECIFICATIONS

Weight capacity	136 kg (21 Stone)
Maximum speed	Up to 5.5 km/h (3.5 mph)
Ground clearance	4.45 cm (1.75")
Turning radius	58 cm (22.75")
Overall length	96 cm (37.75")
Overall width	55 cm (21.5")
Wheels	Drive: 20 cm (8") solid
Front anti-tips	13 cm (5") solid
Rear casters	8 cm (3") solid
Suspension	Limited
Drive train	Two-motor, in-line, rear-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	40 amp, PG GC controller
Specialty controls	No
Battery charger	Off-board, 5 amp (standard)
Per-charge range	Up to 24 km (Up to 15 miles)
Battery requirements	(2) 12 volt, 30 AH
Battery size	30 AH
Battery weight	11 kg (24.5 lbs.) each
Base weight	32 kg (70 lbs.)
Standard seat weight	14 kg (30 lbs.)
Max. seat dimensions	46 cm x 41 cm (18" x 16")
Warranty	5-year limited warranty on frame; 1-year limited warranty on electronics; 1-year limited warranty on drive motors

COLOR CHOICES



Red



Blue

FEATURES

- 30 AH batteries for greater per charge range
- In-line motor technology for increased torque and efficiency
- Tight turning radius of 58 cm (22.75") for tight space manoeuvrability
- Solid tires for worry free ride
- 40 amp PG GC controller
- 136 kg (21 Stone) weight capacity
- 55 cm (21.5") overall width
- 5 amp off-board charger
- Full length padded armrests

OPTIONS

- Cup holder
- Rear basket

Jazzy® Go-2
shown in Blue



Pride[®]
Mobility Products Ltd.

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.com



The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.